

Fiberglass Pocket Filter

FILTRATION GRADE **M5** **M6** **F7** **F8** **F9**



PRODUCT FEATURES

- ▶ Filter material is glass fiber, long service life.
- ▶ Enhanced structure, good filtration performance, large dust capacity.
- ▶ Temperature resistance 150°C, good flame retardancy, up to UL-2 grade standard.
- ▶ Frame: galvanized frame, aluminum frame.

USING

- ▶ Main filter of ventilation and air conditioning system, pre-filter of ventilation and air conditioning system for clean room.

TECHNICAL DATA

Filtration Grade	Dimension (mm) W x H x D	Number of Bags	Filtration Area (m ²)	Rated Air Volume (m ³ /h)	Initial Pressure Drop (Pa)	Final Resistance Recommended (Pa)
M5	287 x 595 x 550	3	2.12	1000	55	200
	595 x 595 x 550	6	3.86	2000	55	
	595 x 595 x 600	8	5.68	2950	55	
M6	287 x 595 x 550	3	2.12	1000	70	250
	595 x 595 x 550	6	3.86	2000	70	
	595 x 595 x 600	8	5.68	2500	70	
F7	287 x 595 x 550	3	2.12	1000	100	300
	595 x 595 x 550	6	3.86	2000	100	
	595 x 595 x 600	8	5.68	2950	100	
F8	287 x 595 x 550	3	2.12	1000	130	450
	595 x 595 x 550	6	3.86	2000	130	
	595 x 595 x 600	8	5.68	2950	130	
F9	287 x 595 x 550	3	2.12	1000	145	450
	595 x 595 x 550	6	3.86	2000	145	
	595 x 595 x 600	8	5.68	2950	145	

★ Data may change without notice. Other specifications and thickness are available on request.