

Guangzhou Clean-link Filtration Technology Co.,Ltd

Add: No. 36, Jianshe South Road, Conghua District, Guangzhou, Guangdong Province, China Tel: +86-020-87469992/87469993/87468869 Fax: +86-020-87469985 E-mail: rita@clean-link.cn info@clean-link.cn

High Temperature Fiberglass Panel Filter

FILTRATION GRADE G3 G4







PRODUCT FEATURES

- ▶ It is made of glass fiber, which is made of non-woven fabric, and is fixed by aluminum expansion net, which is not easy
- ▶ The filter screen has good chemical resistance, strong heat resistance and low moisture absorption.
- ▶ Can withstand high temperature 300°C.
- ► Frame: galvanized frame, aluminum frame, stainless steel frame.

USING

▶ Mainly used for ultra-clean oven, automotive painting and other high-temperature air purification equipment and systems.

TECHNICAL DATA

Filtration Grade	Dimensions (mm) W x H x D	Initial Pressure Drop (Pa)	Final Pressure Drop (Pa)	Testing Wind Velocity (m/s)	Average Weight Efficiency
G3	500 x 500 x 15	45	250	1.0	86%
G3	500 x 500 x 20	45	250	1.0	86%
G4	500 x 500 x 96	60	280	1.0	86%

★ Data may change without notice. Other specifications and thickness are available on request.



