

Laminated Air Filter Media Rolls

FILTRATION GRADE **G3** **G4** **M5** **M6** **F7** **F8** **F9**



PRODUCT FEATURES

- ▶ The use of anti-fracture PET organic synthetic fiber.
- ▶ It is designed as pre-filtration or preliminary filtration for general ventilation equipment and air control systems with heavy pollution.
- ▶ It has the characteristics of high dust holding capacity and low resistance, and it has a long life and is economical and practical.
- ▶ Choice of thickness: 22/44/90mm

USING

- ▶ Used for filter material of metal frame filter such as cardboard frame, aluminum frame and galvanized frame.

TECHNICAL DATA

Filtration Grade	Arrestance	Testing Wind Velocity (m/s)	Initial Pressure Drop (Pa)	Initial Resistance (Pa)	Dust Holding Capacity (g/m ²)
G3	91%	0.2	<15	3	135
G4	91%	0.5	<10	10	135
M5	92%	0.4	<20	20	138
M6	96%	0.3	<30	30	138
F7	97%	0.15	<55	40	142
F8	98%	0.1	<80	50	142
F9	99%	0.1	<90	55	150

Standard size: 610mm x 150m、510mm x 150m Thickness: 3mm

★ Data may change without notice. Other specifications and thickness are available on request.

